



## TECHNICAL SPECIFICATIONS

### Direct Drive Centrifugal Blowers DC Series - Regular size housings

Double inlet – Forward curved

- Blower housing material - galvanized steel G90
- Centrifugal wheel material - galvanneal (satin coat)
- Weld nuts 1/4-20 for motor mounting available
  - @ 8.45" and 9.13" BHC (DC/DCT 916)
  - @ 9.63" and 10.19" BHC (DC/DCT 1020)
- Removable cut-off plate
- Housing supports and motor mounting hardware available
- Further customization (ie. additional mounting holes, discharge flanges etc.) available upon request

Blower Model	Dim A	Dim B	Dim C	Dim D	Dim E	Dim J
DC 916-416-5	10.31	6.81	15.44	14.94	7.19	8.63
DC 916-600-5	10.31	8.25	15.44	14.94	7.19	8.63
DC 916-704-5	10.31	9.18	15.44	14.94	7.19	8.63
DC 916-800-5	10.31	10.50	15.44	14.94	7.19	8.63
DC 916-916-5	10.31	11.81	15.44	14.94	7.19	8.63
DC 1020-416-5	11.38	6.81	17.41	16.56	7.94	9.63
DC 1020-600-5	11.38	8.25	17.41	16.56	7.94	9.63
DC 1020-704-5	11.38	9.69	17.41	16.56	7.94	9.63
DC 1020-800-5	11.38	10.50	17.41	16.56	7.94	9.63
DC 1020-916-5	11.38	12.31	17.41	16.56	7.94	9.63
DC 1020-1020-5	11.38	13.13	17.41	16.56	7.94	9.63

